

## Worked Example #6

Calculate the ideal **Thrust** and **Thrust Coefficient** for a rocket motor operating at 68 atmospheres chamber pressure and exhausts to ambient. The nozzle has a throat diameter of 10mm and has an exit diameter of 35.7mm. The nozzle exit pressure is 1 atmosphere (optimum expansion). The propellant is KNSB.

$P_o$  = Stagnation pressure (chamber pressure), 68 atmospheres

$P_a$  = Ambient pressure, 1 atmosphere

From Technical Notepad #3 (<http://www.nakka-rocketry.net/techs2.html>), KNSB has the following properties:

$k = 1.04$       2-phase flow

The equation for ideal thrust is

$$F = A^* P_o \sqrt{\frac{2k^2}{k-1} \left(\frac{2}{k+1}\right)^{\frac{k+1}{k-1}} \left[1 - \left(\frac{P_e}{P_o}\right)^{\frac{k-1}{k}}\right]} + (P_e - P_a) A_e \quad \text{equation 3}$$

As this is a rather cumbersome equation, the suggested first step is to simplify the calculation by calculating the terms involving “k”

$$\frac{k^2}{k-1} = \frac{(1.04)^2}{1.04-1} = 27.04$$

$$\frac{2}{k+1} = \frac{2}{1.04+1} = 0.9804$$

$$\frac{k+1}{k-1} = \frac{1.04+1}{1.04-1} = 51.0$$

$$\frac{k-1}{k} = \frac{1.04-1}{1.04} = 0.0385$$

The pressure ratio is likewise calculated

$$\frac{P_e}{P_o} = \frac{1}{68} = 0.0147$$

The throat cross-sectional area,  $A^*$ , is

$$A^* = \frac{\pi}{4}(10.0)^2 = 78.5\text{mm}^2$$

The nozzle exit cross-sectional area,  $A_e$ , is

$$A_e = \frac{\pi}{4}(35.7)^2 = 1001\text{mm}^2$$

Since we wish to express the thrust in terms of Newtons (or pounds-force), we must use consistent units. To obtain thrust in Newtons, we use *m-k-s* (metre-kilogram-second) units for all parameters:

$$A^* = 78.5 / 1000^2 = 78.5 \times 10^{-6} \text{ m}^2$$

$$A_e = 1001 / 1000^2 = 0.001 \text{ m}^2$$

Likewise, pressure is converted to  $\text{N/m}^2$

$$P_o = 68 \text{ atm} \times 101325 \frac{\text{N/m}^2}{\text{atm}} = 6.89 \times 10^6 \frac{\text{N}}{\text{m}^2}$$

$$P_e = P_a = 101325 \text{ N/m}^2$$

The ideal thrust may now be calculated. Note that the pressure thrust term in the equation is equal to zero, as  $P_e = P_a$ .

$$F = 78.5 \times 10^{-6} (6.89 \times 10^6) \sqrt{2(27.04)(0.9804)^{51} (1 - (0.0147)^{0.0385})} = \mathbf{929 \text{ N}}$$

(to convert to “pounds force”, we divide Newtons by 4.448, giving  $\mathbf{F= 209 \text{ lbf}}$ )

It is important to always check units for consistency:

$$F = m^2 \frac{\text{N}}{\text{m}^2} \sqrt{\text{dimensionless}} + \left( \frac{\text{N}}{\text{m}^2} - \frac{\text{N}}{\text{m}^2} \right) m^2$$

Therefore

$$F = \cancel{m^2} \frac{\text{N}}{\cancel{\text{m}^2}} \sqrt{\text{dimensionless}}$$

Units are confirmed to be correct (N.)

The equation for Thrust Coefficient is:

$$C_f = \sqrt{\frac{2k^2}{k-1} \left(\frac{2}{k+1}\right)^{\frac{k+1}{k-1}} \left[1 - \left(\frac{P_e}{P_o}\right)^{\frac{k-1}{k}}\right]} + \frac{(P_e - P_a) A_e}{P_o A^*} \quad \text{equation 5}$$

Note that the term inside the square root sign is identical to that of the thrust equation. Also note that the pressure term in the equation is equal to zero, as  $P_e = P_a$ .

$$C_f = \sqrt{2(27.04)(0.9804)^{51} (1 - (0.0147)^{0.0385})} = \mathbf{1.72}$$

A check of the units will confirm that  $C_f$  is dimensionless as expected.

*Compare these values for a nozzle with **optimum expansion** to those values obtained in Worked Example #5.*